

**METHOD AND APPARATUS FOR SCHEDULING FORWARD DATA LINK
TRANSMISSIONS IN CDMA/HDR NETWORKS**

I. Technical Field

This application relates generally to communication systems
5 and, more particularly, to a method and apparatus for scheduling
data transmissions in communication networks.

II. Background

Referring to Figs. 1, 2a, 2b, and 3, an illustrative
embodiment of a conventional code division multiple access/high
10 data rate (CDMA/HDR) communication network 10 may include a
packet data service node (PDSN) 12 that is operably coupled to
the Internet 14 and a base station controller (BSC) 16 that is
operably coupled to access points (APs) 18a, 18b, and 18c. Access
terminals (ATs) 20a, 20b, and 20c in turn may be operably coupled
15 to one or more of the APs 18a, 18b, and 18c.

As will be recognized by persons having ordinary skill in
the art, a CDMA/HDR communication network typically utilizes a
combination of time division multiple access (TDMA) and CDMA. In
an illustrative embodiment, each communication channel is shared
20 among several users, but on an as-needed basis rather than a
fixed time slot as in TDMA. An example of a CDMA/HDR
communications network is the wireless communication network
available from Qualcomm, Inc. that, in an illustrative
embodiment, provides a 2.4 Mbps data rate in a standard 1.25 MHz
25 CDMA bandwidth.

During operation of the network 10, in an illustrative
embodiment, an active set 22 of APs may communicate with the AT
20a utilizing a wireless forward communication link 24 and a
wireless reverse communication link 26. In an illustrative
30 embodiment, at any given time period, only one of the APs in the
active set 22 may communicate with the AT 20a in the forward
communication link 24. By contrast, in the reverse communication

link 26, the AT 20a may communicate with one or more of the APs in the active set 22.

Furthermore, during operation of the network 10, in an illustrative embodiment, in the forward communication link 24, the APs 18 may transmit a power control signal, a pilot signal, and/or a data payload to the ATs 20 using a power control channel 24a, a pilot channel 24b, and/or a data payload channel 24c, respectively. In an illustrative embodiment, the power control signal controls the power of the signals transmitted by the corresponding AT 20. Thus, in this manner, the power level of signals transmitted by a particular AT 20 is controlled by one or more of the APs 18. In an illustrative embodiment, in the reverse communication link 26, the ATs 20 may transmit data rate control signals to the APs 18 using a data rate control channel 26a. In an illustrative embodiment, the data rate control signal controls the maximum rate of data transmitted by the corresponding AP 18 to a particular AT 20 as a function of the carrier to interference ratio (C/I) for the pilot signal transmitted by the corresponding AP to the particular AT. Thus, in this manner, the maximum rate of data transmission from a particular AP 18 to a particular AT 20 is controlled as a function of the calculated C/I for the pilot signal that was transmitted from the particular AP 18 to the particular AT 20.

In a typical CDMA/HDR network, as illustrated in Fig. 3, the AP 18a may service a plurality of ATs, 20a and 20b. Conventional methods of scheduling the transmission of data from the AP 18a to the ATs, 20a and 20b, utilize a proportional fairness criteria in which a proportional fairness index is calculated for each forward communication link between the AP and the ATs. The proportional fairness index is typically calculated by dividing the peak data transmission rate by the historical average data transmission rate for some predetermined time period for each of the forward communication links between the AP 18a and the ATs, 20a and 20b. The peak data transmission rate is typically equated to the maximum data transmission rate value

generated by the ATs, 20a and 20b, as a function of the calculated C/I for the forward communications link and transmitted by the ATs to the AP 18a using the data rate control signal. The AP 18a may then transmit data to the ATs, 20a and 20b, based upon the proportional fairness index values calculated for each forward communication link. Typically, the AP 18a may then schedule transmission of data within an available time slot to the AT having the highest proportional fairness index.

The scheduling of data transmission provided by using the proportional fairness criteria suffers from a number of drawbacks. For example, the proportional fairness criteria does not work very well when not enough data is in the queue to fully utilize the available physical packet layer size. This could happen, for example, when there is a low data transmission rate at the traffic origination point or a bottleneck in the network, or where the data being transmitted is the remaining small amount of a data burst.

The present invention is directed to improving the scheduling of data transmissions in the forward communication links in CDMA/HDR communication networks.

III. Summary

According to one aspect of the present invention, a method of scheduling the transmission of data from an access point to a plurality of access terminals serviced by the access point using the corresponding forward communication links between the access point and the access terminals in a CDMA/HDR communications network is provided that includes the access point calculating a scheduling parameter for each of the forward communication links and access terminals as a function of a plurality of operating parameters, and the access point scheduling data for transmission to the access terminal having the largest scheduling parameter.

According to another aspect of the present invention, a communications network is provided that includes a plurality of access terminals, and an access point operably coupled to the

access terminals by a plurality of corresponding forward communication links. The access point is adapted to: calculate a scheduling parameter for each of the forward communication links and access terminals as a function of a plurality of operating
5 parameters, and schedule data for transmission to the access terminal having the largest scheduling parameter.

According to another aspect of the present invention, a computer program for scheduling the transmission of data from an access point to a plurality of access terminals serviced by the
10 access point using the corresponding forward communication links between the access point and the access terminals in a CDMA/HDR communications network is provided that includes instructions for: the access point calculating a scheduling parameter for each of the forward communication links and access terminals as a
15 function of a plurality of operating parameters, and the access point scheduling data for transmission to the access terminal having the largest scheduling parameter.

According to another aspect of the present invention, a communications network is provided that includes a plurality of
20 access terminals, an access point operably coupled to the access terminals by a plurality of corresponding forward communication links, means for calculating a scheduling parameter for each of the forward communication links and access terminals as a function of a plurality of operating parameters, and means for
25 scheduling data for transmission to the access terminal having the largest scheduling parameter.

The present embodiments of the invention provide a number of advantages. For example, the use of the frame utilization as a weighting factor in the calculation of the scheduling parameter
30 P permits the scheduling parameter to reflect the degree to which the frame is utilized for each forward transmission link. In this manner, the scheduling of data transmissions between the access point and the access terminals is more efficient. Furthermore, the use of a plurality of weighting factors permits
35 the calculation of the scheduling factor P to reflect the full

002027 "0322.630

range of relevant factors that effect and influence the scheduling of data transmission. In this manner, the scheduling of data transmissions is more efficient and more flexible.

IV. Brief Description of the Drawings

Fig. 1 is a schematic view of an illustrative embodiment of a CDMA/HDR communication network.

Fig. 2a is a schematic view of an illustrative embodiment of the communication during the forward communication link between the access points and access terminals of the network of Fig. 1.

Fig. 2b is a schematic view of an illustrative embodiment of the communication during the reverse communication link between the access points and access terminals of the network of Fig. 1.

15 Fig. 3 is a schematic view of an illustrative embodiment of
a CDMA/HDR communication network in which an access point
services a plurality of access terminals.

Fig. 4 is a flow chart illustration of an illustrative embodiment of a method of scheduling the transmission of data in the forward communication links between an access point and a plurality of access terminals in a CDMA/HDR network.

V. Detailed Description

Referring to Fig. 4, the reference numeral 100 refers, in
25 general to a method of scheduling the transmission of data
between an access point and a plurality of access terminals in
the CDMA/HDR communications network 10 in which an AP 18
servicing a plurality of ATs 20 calculates a scheduling parameter
P for each of the forward links between the AP and the ATs using
30 the following equation in step 102:

$$P_i = (R_{MAXi} / R_{AVGi}) * U_{FRAMEi} \quad (1)$$

where P_i = the scheduling parameter for the
ith forward communication link
for the corresponding ith AT;
 R_{MAXi} = the maximum data transmission
rate for the ith forward
communication link for the
corresponding ith AT;
 R_{AVGi} = the average data transmission
rate for the ith forward
communication link for the ith
corresponding ith AT for a
predetermined time period; and
 U_{FRAMEi} = the frame utilization for the ith
forward communication link for the
corresponding ith AT.

In an exemplary embodiment, the maximum data transmission
rate for the ith forward communication link R_{MAXi} is substantially
equal to the maximum data transmission rate transmitted to the AP
18 by the corresponding AT 20. In an exemplary embodiment, the
frame utilization for the ith forward communication link U_{FRAMEi}
calculated using the following equation:

$$U_{FRAMEi} = DPA_i / PS_i \quad (2)$$

where DPA_i = the size of the data payload
available to send to the ith AT;
and
 PS_i = the physical layer packet size
corresponding to R_{MAXi} .

The AP 18 may then schedule data for transmission to the AT
20 having the highest scheduling parameter P in step 104. The AP
18 may then transmit a data packet to the scheduled AT 20 in step
106. The AP 18 may then repeat steps 102, 104 and 106. In this
manner, the scheduling parameter P is generated using a plurality
of indices. Furthermore, the use of the frame utilization U_{FRAME}
as a weighting factor in the generation of the scheduling

parameter P ensures that the scheduling of data transmissions over the forward communication links between the AP 18 and the ATs 20 takes into account the frame utilization and thereby more efficiently schedules the transmission of data.

5 More generally, the scheduling parameter P may be calculated using the following equation:

$$P_i = (R_{MAXi} / R_{AVGi}) * WF_1 * WF_2 * ... * WF_j \quad (3)$$

10 where P_i = the scheduling parameter for the
ith forward communication link
for the corresponding ith AT;
 R_{MAXi} = the maximum data transmission
rate for the ith forward
communication link for the
corresponding ith AT;
15 R_{AVGi} = the average data transmission
rate for the ith forward
communication link for the
corresponding ith AT for a
predetermined time period; and
20 $WF_1...WF_j$ = weighting factors to be used to
generate the scheduling
parameter P, where j varies from
1 to N.

25 In an exemplary embodiment, the weighting factors may include one or more of the following: the frame utilization U_{FRAMEi} , and the priority of the data to be sent using the ith forward communication link $Priority_i$. In an exemplary embodiment, all of the weighting factors WF_j are expressed as a fraction that can vary from zero to one. In a further exemplary
30 embodiment, one or more of the weight factors WF_j are also normalized.

The present embodiments of the invention provide a number of advantages. For example, the use of the frame utilization as a weighting factor in the calculation of the scheduling parameter

5 Furthermore, the use of a plurality of weighting factors permits the calculation of the scheduling factor P to reflect to full range of relevant factors that effect and influence the scheduling of data transmission. In this manner, the scheduling of data transmissions is more efficient and more flexible.

It is understood that other modifications, changes and substitutions are intended in the foregoing disclosure and in some instances some features of the disclosure will be employed without corresponding use of other features. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the disclosure.